

# INDEX

## About the electronic part capacitor

- Product Line-up Table ..... 2
- Series System Diagram ..... 4
- Guidelines and Precautions for Use ..... 6
- Environmental Consideration /  
Surface Mount Type Recommended Land Pattern ..... 10
- Soldering Condition / Recommended Reflow Condition ..... 11
- Packing Specifications ..... 12
- Ripple Current Frequency Coefficient ..... 15
- Anti-vibration Structure** ..... 16

- Aluminum Electrolytic Capacitors with Hybrid Conductive Polymer **EP-cap** ..... 17

- Aluminum Electrolytic Capacitors ..... 27

### Series integration

On new order, please order from Integrated series.

Discontinued series	Integrated series	Feature
<b>CE-EX</b>	<b>HVA</b>	Hybrid Conductive Polymer, Super Low ESR
<b>CE-GS</b>	<b>CE-GA</b>	Surface mount type, 5.4mm height, low impedance
<b>CE-GX</b>	<b>CE-AX</b>	Surface mount type, low impedance, high-reliability
<b>CE-FC</b>	<b>CE-FD</b>	Surface mount type, 4.5mm height
<b>CE-PX</b>	<b>CE-PC</b>	Surface mount type, 125°C Long life
<b>MV-AZ</b>	<b>ME-CZ</b>	105°C Standard
<b>MV(ME)-FA</b>	<b>ME-CZ</b>	105°C Standard
<b>MV-EG,GX</b>	<b>ME-AX</b>	105°C low impedance, high-reliability
<b>MV-HW</b>	<b>ME-HC</b>	85°C Standard
<b>MV-HPS</b>	<b>ME-HPC</b>	85°C Miniature, standard (mid.&high voltage)
<b>MV-NPD,NPDW</b>	<b>ME-HWN</b>	85°C Bi-polar (miniature, standard)